
Pipe clamp Sigma, black, lined

EPDM



Pipe clamp Sigma rubber black



Pipe clamp Sigma

Specification

Application area:	Pipe clamp for fastening pipes.
Closure:	Sigma safety quick-closure

Technical data

Material:	Steel
Surface:	galvanized
Sound insulation lining:	Rubber EPDM
Colour sound insulation lining:	black
Temperature resistance:	-35 up to 100 °C
Insulation thickness:	3 mm

Remark: Determination of the permissible load using static methods from the breaking loads and taking into account a maximum permissible deformation of 1,5 mm or 2% of the maximum expandable pipe diameter.

Clamping range [mm]	OD [inch]	Connection	Closure screw	Material dimension [mm]	Load F_Z [kN]	Height H [mm]	Connection height A [mm]	Width B [mm]	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
6-10		M8	M5	20x1,0	0,45	23-27	12	33	0,0220	100	14510150
12-15	1/4	M8	M5	20x1,0	0,45	30-33	12	41	0,0260	100	14510151
16-19	3/8	M8	M5	20x1,0	0,45	34-37	12	45	0,0290	100	14510191
25-29	3/4	M8	M5	20x1,0	0,45	43-47	12	56	0,0360	100	14510291
32-35	1	M8	M5	20x1,0	0,45	50-53	12	62	0,0420	100	14510351
40-44	1 1/4	M8	M5	20x1,0	0,45	58-62	12	71	0,0580	50	14510441
48-52	1 1/2	M8	M5	20x1,5	0,80	66-70	12	80	0,0790	50	14510521
53-57		M8	M5	20x1,5	0,80	71-75	12	85	0,0860	50	14510571
58-60	2	M8	M5	20x1,5	0,80	76-79	12	89	0,0910	50	14510601
20-23	1/2	M8	M5	20x1,0	0,45	38-41	12	51	0,0330	100	14510231