Pipe clamp Talis, lined

EPDM



Pipe clamp Talis

Specification

Application area:	Pipe clamp for fastening pipes.
Closure:	Screw coupling

Technical data

Material:	Steel
Surface:	galvanized
Sound insulation lining:	Rubber EPDM
Colour sound insulation lining:	black
Temperature resistance:	-35 up to 100 °C
Insulation thickness:	3 mm

Clamping range [mm]	OD [inch]	Connection	Closure screw	Material dimension [mm]	Load F_Z [kN]	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
12-14	1/4	M8	M5	20x1,0	1,25	0,0310	100	101234012
15-19	3/8	M8	M5	20x1,0	1,25	0,0330	100	101234015
20-23	1/2	M8	M5	20x1,0	1,25	0,0370	100	101234020
24-28	3/4	M8	M5	20x1,0	1,25	0,0400	100	101234026
31-35	1	M8	M5	20x1,0	1,25	0,0440	100	101234032
38-43	1 1/4	M8	M5	20x1,0	1,25	0,0480	50	101234040
48-51	1 1/2	M8	M5	20x1,0	1,25	0,0540	50	101234048
52-56		M8	M6	20x1,2	1,30	0,0630	50	101234052
57-63	2	M8/M10	M6	20x1,2	1,30	0,0770	50	101234057
63-67		M8/M10	M6	20x1,5	1,50	0,0850	50	101234063
70-73		M8/M10	M6	20x1,5	1,50	0,0910	50	101234070
74-80	2 1/2	M8/M10	M6	20x1,5	1,50	0,101	50	101234074
83-91	3	M8/M10	M6	20x1,5	1,50	0,112	50	101234083
108-114	4	M8/M10	M6	25x1,5	2,00	0,177	50	101234108
120-125		M10/M12	M6	25x2,0	3,00	0,222	25	101234125
130-136		M10/M12	M6	25x2,0	3,00	0,238	25	101234130
136-142	5	M10/M12	M6	25x2,0	3,00	0,250	25	101234136
159-163		M10/M12	M6	25x2,0	3,00	0,280	25	101234159
165-169	6	M10/M12	M6	25x2,0	3,00	0,310	25	101234165