


SIMA-Cramp grip connector



SIMA-Cramp grip connector DN 50 up to 125




Grip connector SIMA-Cramp




Grip connector SIMA-Cramp


SIMA-Cramp grip connector DN 150 up to 250



Grip connector SIMA-Cramp



Grip connector SIMA-Cramp

22 1130 3 94
MPA NRW

Specification

Application area: Grip connector for drain pipes without sleeves in connection with connector SIMA RAPID.

max. pressure load: 5 bar

Technical data

Material: Steel

Surface: galvanized

* Test certificate no. P 11 0003361 applies to DN 80

Nominal width DN [mm]	Outer pipe diameter [mm]	Specification	Tightening torque [Nm]	Height D [mm]	Width pipe clamp strap B [mm]	Length S [mm]	max. pressure load [bar]	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
50	58	two-part	50	75	79	113	5	0,447	20	4472500
70	78	two-part	15	99	92	134	5	0,576	20	4472705
80	83	two-part	20	102	74	138	5	0,800	10	4472805 *
100	110	two-part	15	130	103	174	5	0,992	10	4473000
125	135	two-part	20	154	103	202	5	1,11	10	44732561
200	210	three-part	20	236	120	244	5	2,57	5	4474000
250	274	three-part	30	300	133	308	5	3,90	4	4474508