
## Fixpoint support for downstream piping



Fixpoint support for downstream piping (mounted)

**Specification**

Application area: Brackets for the manufacture of a support for sewage downpipes.


**Technical data**

| | |
|---|---|
| Material: | Steel |
| Surface: | galvanized |
| Sound insulation lining: | TPE |
| Temperature resistance: | -35 up to 100 °C |
| Thickness material sound insulation lining: | 6 mm |

Remark: To prevent the pipe from slipping a flange or similar should be placed above the pipe clamp.

| Nominal width DN [mm] | Outer pipe diameter [mm] | Distance measure a [mm] | Hole distance b [mm] | Wall distance Wa [mm] | Elongated hole [mm] | Load F1 [kN] | Load F2 [kN] | Weight [kg/pc] | Packing unit [pcs.] | Part-No. |
|---|---|---|---|---|---|---|---|---|---|---|
| **80** | 83 | 140 | 55 | 75-260 | 15x11 | 1,44 | 0,72 | 1,63 | 1 | 4500800 |
| **100** | 110 | 165 | 55 | 75-260 | 15x11 | 1,44 | 0,72 | 1,61 | 1 | 4501000 |
| **150** | 160 | 230 | 80 | 100-300 | 15x11 | 4,16 | 2,08 | 2,79 | 1 | 4501500 |
| **200** | 210 | 280 | 85 | 125-315 | 20x14 | 6,64 | 3,32 | 4,08 | 1 | 45020045 |

Loading condition 1




Loading condition 2

