
Pipe clamp Trabant, lined

EPDM



Pipe clamp Trabant



Pipe clamp Trabant

Specification

Application area:	Pipe clamp for fastening pipes.
Closure:	Snap-in closure

Technical data

Material:	Steel
Surface:	galvanized
Sound insulation lining:	Rubber EPDM
Colour sound insulation lining:	black
Temperature resistance:	-35 up to 100 °C
Insulation thickness:	4,5 mm

Remark: Suitable connection adapter see chapter 1. Permissible loads in the event of fire see chapter 15. Determination of the permissible load using static methods from the breaking loads and taking into account a maximum permissible deformation of 1,5 mm or 2% of the maximum expandable pipe diameter.

* not certified acc. to RAL GZ-656

Clamping range [mm]	OD [inch]	Connection	Closure screw	Material dimension [mm]	Load F_Z [kN]	Height H [mm]	Connection height A [mm]	Width B [mm]	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
12-15		M8/M10	M6	20x1,0	0,29	40-43	22	59	0,0510	100	042615101
16-20	3/8	M8/M10	M6	20x1,0	0,29	43-48	22	64	0,0540	100	042620101
21-25	1/2	M8/M10	M6	20x1,0	0,29	48-53	22	69	0,0580	100	042625101
26-30	3/4	M8/M10	M6	20x1,0	0,29	53-58	22	75	0,0640	100	042630101
32-37	1	M8/M10	M6	20x1,0	0,29	60-65	22	81	0,0660	100	042637101
42-46	1 1/4	M8/M10	M6	20x1,5	0,89	71-75	23	92	0,0940	50	042646101
48-52	1 1/2	M8/M10	M6	20x1,5	0,89	76-81	23	98	0,101	50	042652101
54-58		M8/M10	M6	20x1,5	0,89	82-87	23	104	0,107	50	042658101
60-65	2	M8/M10	M6	20x1,5	0,89	88-94	23	111	0,114	50	042665101
70-76		M8/M10	M6	25x1,5	0,89	98-104	22	122	0,150	50	042672101
77-83	2 1/2	M8/M10	M6	25x1,5	0,89	104-111	22	127	0,155	50	042677101
85-90	3	M8/M10	M6	25x2,0	1,50	114-119	23	134	0,202	50	0426901
108-114	4	M8/M10	M6	25x2,5	1,90	142-148	26	166	0,253	50	0427141
121-125		M10/M12	M6	25x2,5	2,20	156-162	27	176	0,313	25	04272251 *
132-136		M10/M12	M6	25x2,5	2,20	167-173	27	187	0,337	25	04272361 *
137-141	5	M10/M12	M6	25x2,5	2,20	172-178	27	192	0,343	25	04272411 *
159-163		M10/M12	M6	25x2,5	2,20	194-200	27	215	0,388	25	04272631 *
164-168	6	M10/M12	M6	25x2,5	2,20	199-205	27	220	0,398	25	04272681 *
196-202		M10/M12	M6	25x2,5	2,20	232-238	27	255	0,576	10	04273021 *