
Nail anchor N


Nail anchor N



Nail anchor N


Nail anchor N-M

Product description

- Metal anchor for high loads
- Combines the advantages of a bolt anchor with even simpler installation
- Quick, easy installation: simply hammer in
- European Technical Assessment in concrete
- Approved for use under the influence of fire
- Reduced anchoring depth of just 25 mm for low drilling effort
- Very small edge and center distances
- Just one product for two applications: M8/M10 stepped thread (N-M)

Specification

Application area: For multiple fixings in cracked concrete C12/15 - C50/60, e.g. ceiling suspensions, piping, cladding, cable trays and rail fastening.

Delivery time: V4A - 3 working days, ex works

Remark: For load values see end of chapter 7. The reduced loads must be taken into account for reduced anchoring depths.

Series	Dimension [mm]	Material	Clamping thickness [mm]	Drilling hole [mm]	Depth of anchoring [mm]	Length dowel [mm]	SW	Female thread	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
N	6-5-10/49	Steel, galv.	5	6x40	30	49			0,0140	200	221861010701
N	6-5/49	Stainless steel, V4A	5	6x40	30	49			0,0140	200	222861010541
N-M	6-25	Steel, galv.		6x35	25	58	13	M8/M10	0,0275	100	221860310101
N-M	6-30	Steel, galv.		6x40	30	63	13	M8/M10	0,0285	100	221860315101

Installation advise nail anchor N and N-M

