## Hollow core anchor Easy



Hollow core anchor Easy

Z-21.1-1785

### Product description

- For use in prestressed concrete hollow core slabs and reinforced concrete hollow core slabs
- Installation on floor and ceiling side possible
- General building authority approval for anchoring individual dowels in prestressed concrete hollow core slabs, both from the floor and the ceiling side
- Generally approved by building authorities as a multiple fastening for anchoring lightweight suspended ceilings and comparable anchorages
- Approved for use in dry indoor areas
- Fire protection tested
- No drill hole cleaning required for processing and installation
- Approved for the installation of sprinkler systems

### Specification

Application area: Pre-stressed hollow concrete slabs concrete C45/55.

### Technical data

Material: Steel

Surface: galvanized

Remark: Load values see end of chapter 7.

| Description | Drill Ø [mm] | Thread | Drill hole depth [mm] | Length sleeve [mm] | Setting depth [mm] | Tightening torque [Nm] | Weight [kg/pc] | Packing unit [pcs.] | Part-No. |
|---|---|---|---|---|---|---|---|---|---|
| **Easy M8** | 12 | M8 | 55 | 35 | 47 | 20 | 0,0144 | 50 | 221851100101 |
| **Easy M10** | 12 | M10 | 60 | 40 | 55 | 30 | 0,0332 | 50 | 221851200101 |

## Installation advise hollow core anchor Easy

