Toggle bolts



KV 8


K 8


K 10


BIG-M

Product description

- For use with cavity walls, hollow ceilings, suspended ceilings and various sandwich elements
- Wide-area pressure distribution is guaranteed
- Safe and quick installation
- High loads
- Immediately loadable
- For stationary fire protection systems, the provisions of VdS or FM apply (for pipes up to max. DN 2") (KV 8 and KV 10)
- VDS (KV 8 and KV 10) and FM approval (KV 10)
- For all cavity fastenings where maximum strength is required (BIG M)

Specification

Application area: For cavity walls, suspended ceilings and cavity walls.

Technical data

Material: Steel

Surface: gavanized, chromated

Description	Threaded rod type	Drill Ø [mm]	min. width of hollow [mm]	Breaking loads [kN]	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
KV	M8x100	22	90	20	0,113	50	2120081
KV	M8x200	22	90	20	0,146	25	2120082
KV	M8x300	22	90	20	0,177	25	2120083
KV	M8x500	22	90	20	0,240	25	2120085
KV	M10x100	25	90	20	0,137	25	212010100
K	M8x100	20	75	13	0,0821	100	2128306
K	M10x180	30	140	12	0,210	25	2120518
BIG-M	M10x180	30	90	11	0,217	25	2123517