

Pipe clamp Maxima PSM 3G, unlined



Pipe clamp Maxima PSM 3G



Pipe clamp Maxima PSM 3G

Specification

Application area:	Clamp pipe clip for fixpoint FGL. Pipe clamp for fixing pipes.
Closure:	Pendulum stick nuts

Technical data

Material:	Steel
Surface:	galvanized
Sound insulation lining:	unlined
Tightening torque:	5 Nm

Remark: Tightening torques of the screw plugs and axial forces (permissible load Fy) of the pipe clamp only apply to steel pipes with standard wall thickness. Determination of the permissible load using static methods from the breaking loads and taking into account a maximum permissible deformation of 1,5 mm or 2% of the maximum expandable pipe diameter. Other dimensions or version with sound insulation available in request.

Clamping range [mm]	Connection	Closure screw	Material dimension [mm]	Load F_Z [kN]	Load F_Y [kN]	Height H [mm]	Connection height A [mm]	Width B [mm]	Center distance S [mm]	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
20-23	M8/M10 + 1/2"	M8	25x3	3	0,7	41-44	23	73	49	0,216	1	0069047
25-29	M8/M10 + 1/2"	M8	25x3	3	0,7	46-50	23	80	56	0,225	1	0069049
30-35	M8/M10 + 1/2"	M8	25x3	3	0,7	51-56	23	87	63	0,235	1	0069053
36-40	M8/M10 + 1/2"	M8	25x3	3	0,7	57-61	23	92	68	0,246	1	0069081
41-46	M8/M10 + 1/2"	M8	25x3	3	0,7	62-67	23	98	74	0,258	1	0069097
48-55	M8/M10 + 1/2"	M8	25x3	3	0,7	74-81	23	107	83	0,268	1	0069127
57-61	M8/M10 + 1/2"	M8	25x3	3	0,7	83-87	23	114	90	0,284	1	0069143