
Pipe clamp Titan HD, lined

TPE



Pipe clamp Titan HD



Pipe clamp Titan HD

Specification

Application area:	Pipe clamp, sound-insulated for fastening pipes in the heavy load range.
Closure:	Screw coupling

Technical data

Material:	Steel
Surface:	galvanized
Sound insulation lining:	TPE
Colour sound insulation lining:	black
Temperature resistance:	-35 up to 100 °C
Insulation thickness:	6 mm

Delivery time: 5 - 8 working days ex works. Exchange and return are excluded.

Remark: Suitable connection adapter see chapter 1. Permissible loads in the event of fire see chapter 15. Custom-made products on request. Determination of the permissible load using static methods from the breaking loads and taking into account a maximum permissible deformation of 1,5 mm or 2% of the maximum expandable pipe diameter.

* not certified acc. to RAL

OD [mm]	OD [inch]	Connection	Closure screw D	Material dimension [mm]	Load F_Z [kN]	Height H [mm]	Connection height A [mm]	Width B [mm]	Center distance S [mm]	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
60		M12	M12	50x5	3,2	94	22	149	120	0,888	1	0066497
64		M12	M12	50x5	3,2	97	22	154	125	0,918	1	0066504
76	2 1/2	M12	M12	50x5	3,2	109	22	166	137	1,01	1	0066508
89	3	M12	M12	50x5	3,2	122	22	179	150	1,11	1	0066510
108		M12	M12	50x5	3,2	141	22	199	170	1,25	1	0066516
110		M12	M12	50x5	3,2	143	22	201	172	1,26	1	0066532
114	4	M12	M12	50x5	3,2	147	22	205	176	1,29	1	0066559
125		M12	M12	50x5	3,2	158	22	216	187	1,38	1	0066583
127		M12	M12	50x5	3,2	160	22	218	189	1,39	1	0066591
133		M12	M12	50x5	3,2	166	22	224	195	1,44	1	0066605
135		M12	M12	50x5	3,2	168	22	226	197	1,45	1	0066613
140	5	M12	M12	50x5	3,2	173	22	231	202	1,49	1	0066621
152		M12	M12	50x5	3,2	185	22	243	214	1,58	1	0066648
160		M12	M12	50x5	3,2	193	22	251	222	1,64	1	0066680
165	6	M12	M12	50x5	3,2	198	22	256	227	1,68	1	0066699
168		M12	M12	50x5	3,2	201	22	259	230	1,70	1	0066710
177		M12	M12	50x5	11,5	210	22	268	239	1,77	1	0066737
180		M12	M12	50x5	11,5	213	22	271	242	1,79	1	0066753
194		M12	M12	50x5	11,5	227	22	286	257	1,89	1	0066761
200		M12	M12	50x5	11,5	233	22	292	263	1,94	1	0066788
210		M12	M12	50x5	11,5	243	22	302	273	2,01	1	0066818
219	8	M12	M12	50x5	11,5	252	22	311	282	2,08	1	0066826
225		M12	M12	50x5	11,5	258	22	317	288	2,13	1	0066842
245		M12	M12	50x5	11,5	278	22	337	308	2,28	1	0066877
267		M12	M12	50x5	11,5	300	22	359	330	2,44	1	0066893
273	10	M12	M12	50x5	11,5	306	22	365	336	2,49	1	0066907