
Sprinkler pipe clamp HDC



Sprinkler pipe clamp HDC



Sprinkler pipe clamp HDC

Specification

Application area:	Pipe clamp with connection thread according to sprinkler guidelines for Sprinkler systems.
Installation advise:	Locking screws are secured by a plastic washer.
Specification:	two-part
Brand:	Jiangmen Eurofix

Technical data

Material:	Steel
Surface:	galvanized
Sound insulation lining:	unlined
Tightening torque:	3 Nm

Remark: Tightening torque for closing screw, see chapter 15

* Complies with the requirements of the “VdS CEA 4001 - Planning and installation” guideline

Clamping range [mm]	OD [inch]	Certification	Connection	Material dimension [mm]	Closure screw	Load F_Z [kN]	Height H [mm]	Connection height A [mm]	Width B [mm]	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
20 - 24	1/2	VdS	M8	30x2,5	M8	2,5	42	15	66	0,141	50	47300020
25 - 30	3/4	VdS	M8	30x2,5	M8	2,5	50	17	71	0,148	50	47300025
31 - 35	1	VdS	M8	30x2,5	M8	2,5	55	16	77	0,155	50	47300031
40 - 45	1 1/4	VdS	M8	30x2,5	M8	1,5	65	16	88	0,174	50	47300040
48 - 53	1 1/2	VdS	M8	30x2,5	M8	2,5	73	16	96	0,192	50	47300048
60 - 65	2	VdS	M8	30x2,5	M8	2,5	85	16	108	0,217	25	47300061
20 - 24	1/2	VdS	M10	30x2,5	M8	2,5	44	17	66	0,141	50	47300022
25 - 30	3/4	FM/VdS	M10	30x2,5	M8	2,5	52	19	71	0,148	50	47300027
31 - 35	1	FM/VdS	M10	30x2,5	M8	2,5	57	18	77	0,155	50	47300034
40 - 45	1 1/4	FM/VdS	M10	30x2,5	M8	2,5	67	18	88	0,174	50	47300043
48 - 53	1 1/2	FM/VdS	M10	30x2,5	M8	2,5	75	18	96	0,192	50	47300050
60 - 65	2	FM/VdS	M10	30x2,5	M8	2,5	87	18	108	0,217	25	47300060
76 - 81	2 1/2	FM/VdS	M10	30x3,0	M8	3,5	105	20	135	0,292	25	47300076
88 - 93	3	FM/VdS	M10	30x3,0	M8	3,5	117	20	147	0,319	25	47300088
110 - 116	4	FM	M10	30x3,0	M8	3,5	140	20	171	0,365	25	47300110 *
140 - 148	5	FM/VdS	M12	40x4,0	M12	5,0	168	19	216	0,806	10	47300140
167 - 173	6	FM	M12	40x4,0	M12	5,0	193	19	242	0,903	10	47300167 *
219 - 225	8	FM	M16	40x4,0	M12	10,0	248	20	294	1,12	10	47300219