

Pipe clamp Trabant Inox, lined

TPE



Pipe clamp Trabant Inox



Pipe clamp Trabant Inox

Specification

Application area:	Pipe clamp for fastening pipes.
Closure:	Snap-in closure
Closure screw:	M6

Technical data

Material:	Stainless steel
Material type:	V4A
Sound insulation lining:	TPE
Colour sound insulation lining:	black
Temperature resistance:	-35 up to 100 °C
Insulation thickness:	4,5 mm

Delivery time: 2 working days, ex works

Remark: The permissible load was determined using statistical methods from the breaking loads and in compliance with a maximum permissible deformation of 1,5 mm or 2 % of the maximum clampable pipe diameter.

Clamping range [mm]	OD [inch]	Connection	Material dimension [mm]	Load F_Z [kN]	Height H [mm]	Connection height A [mm]	Width B [mm]	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
12-15		M8/M10	20x1,0	0,4	40-43	22,0	59	0,0512	100	051003015
16-20	3/8	M8/M10	20x1,0	0,4	43-48	22,0	64	0,0543	100	051003020
21-25	1/2	M8/M10	20x1,0	0,4	48-53	22,0	69	0,0585	100	051003025
26-30	3/4	M8/M10	20x1,0	0,4	53-58	22,0	74	0,0628	100	051003030
32-37	1	M8/M10	20x1,0	0,4	60-65	22,0	81	0,0675	100	051003037
42-46	1 1/4	M8/M10	20x1,5	0,6	71-75	22,5	92	0,0956	50	051003046
48-52	1 1/2	M8/M10	20x1,5	0,6	76-81	22,5	98	0,103	50	051003052
54-58		M8/M10	20x1,5	0,6	82-87	22,5	104	0,110	50	051003058
60-65	2	M8/M10	20x1,5	0,6	88-94	22,5	111	0,117	50	051003065
70-76		M8/M10	25x1,5	0,7	99-105	22,5	121	0,151	50	051003076
85-90	3	M8/M10	25x2,0	1,0	116-121	23,5	138	0,206	50	051003090
98-102		M10/M12	25x2,5	2,5	132-136	27,0	154	0,264	50	051003102
108-114	4	M10/M12	25x2,5	2,5	142-148	27,0	166	0,289	50	051003114
132-136		M10/M12	25x2,5	2,5	168-172	27,0	188	0,347	25	051003136
137-141	5	M10/M12	25x2,5	2,5	173-177	27,0	193	0,356	25	051003141
159-163		M10/M12	25x2,5	2,5	195-199	27,0	215	0,401	25	051003163
164-168	6	M10/M12	25x2,5	2,5	200-204	27,0	220	0,416	25	051003168