

Pipe clamp stainless steel, lined

TPE



Pipe clamp stainless steel, lined



Pipe clamp stainless steel

Specification

Application area:	Pipe clamp for fastening pipes.
Closure:	Screwed closure

Technical data

Material:	Stainless steel
Sound insulation lining:	TPE
Colour sound insulation lining:	black
Temperature resistance:	-35 up to 100 °C

Delivery time: 2 working days, ex works

Clamping range [mm]	OD [inch]	Connection	Closure screw D	Material dimension [mm]	Insulation thickness [mm]	Load F_Z [kN]	Height H [mm]	Connection height A [mm]	Width B [mm]	Material type	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
15-20	3/8	M8	M6	20x1,5	3,5	0,75	31-35	11	56	V4A	0,0570	50	0498174
21-25	1/2	M8	M6	20x1,5	3,5	0,75	36-40	11	61	V4A	0,0630	50	0498175
26-30	3/4	M8	M6	20x1,5	3,5	0,75	41-45	11	66	V4A	0,0690	50	0498176
31-34	1	M8	M6	20x1,5	3,5	0,75	46-50	11	72	V4A	0,0730	50	0498177
35-40		M8	M6	20x1,5	3,5	0,75	51-56	11	78	V4A	0,0770	50	0498178
41-45	1 1/4	M8	M6	20x1,5	3,5	0,75	58-65	11	86	V4A	0,0840	50	0498179
15-20	3/8	M8	M6	20x1,5	3,5	0,75	31-35	11	56	V2A	0,0560	50	0468174
21-25	1/2	M8	M6	20x1,5	3,5	0,75	36-40	11	61	V2A	0,0630	50	0468175
26-30	3/4	M8	M6	20x1,5	3,5	0,75	41-45	11	66	V2A	0,0680	50	0468176
31-34	1	M8	M6	20x1,5	3,5	0,75	46-50	11	72	V2A	0,0730	50	0468177
35-40		M8	M6	20x1,5	3,5	0,75	51-56	11	78	V2A	0,0760	50	0468178
41-45	1 1/4	M8	M6	20x1,5	3,5	0,75	58-65	11	86	V2A	0,0830	50	0468179
47-52	1 1/2	M10	M6	20x2,0	6,0	0,95	69-74	16	96	V4A	0,133	50	0498210
53-57		M10	M6	20x2,0	6,0	0,95	75-79	16	101	V4A	0,141	50	0498211
58-64	2	M10	M6	20x2,0	6,0	0,95	80-86	16	108	V4A	0,149	50	0498212
65-70		M10	M6	20x2,0	6,0	0,95	87-92	16	114	V4A	0,160	50	0498213
72-80	2 1/2	M10	M6	20x2,0	6,0	0,95	94-102	16	123	V4A	0,171	50	0498214
82-90	3	M10	M6	20x2,0	6,0	0,95	104-112	16	134	V4A	0,186	50	0498215
93-100		M10	M6	20x2,0	6,0	0,95	115-122	16	144	V4A	0,203	50	0498216
102-107		M10	M6	20x2,0	6,0	0,95	124-129	16	152	V4A	0,216	50	0498217
108-116	4	M10	M6	20x2,0	6,0	0,95	130-138	16	160	V4A	0,225	50	0498218
47-52	1 1/2	M10	M6	20x2,0	6,0	0,95	69-74	16	96	V2A	0,132	50	0468210
53-57		M10	M6	20x2,0	6,0	0,95	75-79	16	101	V2A	0,140	50	0468211
58-64	2	M10	M6	20x2,0	6,0	0,95	80-86	16	108	V2A	0,148	50	0468212
65-70		M10	M6	20x2,0	6,0	0,95	87-92	16	114	V2A	0,159	50	0468213
72-80	2 1/2	M10	M6	20x2,0	6,0	0,95	94-102	16	123	V2A	0,169	50	0468214
82-90	3	M10	M6	20x2,0	6,0	0,95	104-112	16	134	V2A	0,185	50	0468215
93-100		M10	M6	20x2,0	6,0	0,95	115-122	16	144	V2A	0,210	50	0468216
102-107		M10	M6	20x2,0	6,0	0,95	124-129	16	152	V2A	0,214	50	0468217
108-116	4	M10	M6	20x2,0	6,0	0,95	130-138	16	160	V2A	0,224	50	0468218