

Pipe clamp stainless steel, lined

TPE



Pipe clamp stainless steel, lined



Pipe clamp stainless steel

Specification

Application area:	Pipe clamp for fastening pipes.
Closure:	Screwed closure

Technical data

Material:	Stainless steel
Sound insulation lining:	TPE
Colour sound insulation lining:	black
Temperature resistance:	-35 up to 100 °C

Delivery time: 2 working days, ex works

Clamping range [mm]	OD [inch]	Connection	Closure screw D	Material dimension [mm]	Insulation thickness [mm]	Load F_Z [kN]	Height H [mm]	Connection height A [mm]	Width B [mm]	Material type	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
15-20	3/8	M8	M6	20x1,5	3,5	0,75	31-35	11	56	V4A	0,0570	50	0498174
21-25	1/2	M8	M6	20x1,5	3,5	0,75	36-40	11	61	V4A	0,0630	50	0498175
26-30	3/4	M8	M6	20x1,5	3,5	0,75	41-45	11	66	V4A	0,0690	50	0498176
31-34	1	M8	M6	20x1,5	3,5	0,75	46-50	11	72	V4A	0,0730	50	0498177
35-40		M8	M6	20x1,5	3,5	0,75	51-56	11	78	V4A	0,0770	50	0498178
41-45	1 1/4	M8	M6	20x1,5	3,5	0,75	58-65	11	86	V4A	0,0840	50	0498179
15-20	3/8	M8	M6	20x1,5	3,5	0,75	31-35	11	56	V2A	0,0560	50	0468174
21-25	1/2	M8	M6	20x1,5	3,5	0,75	36-40	11	61	V2A	0,0630	50	0468175
26-30	3/4	M8	M6	20x1,5	3,5	0,75	41-45	11	66	V2A	0,0680	50	0468176
31-34	1	M8	M6	20x1,5	3,5	0,75	46-50	11	72	V2A	0,0730	50	0468177
35-40		M8	M6	20x1,5	3,5	0,75	51-56	11	78	V2A	0,0760	50	0468178
41-45	1 1/4	M8	M6	20x1,5	3,5	0,75	58-65	11	86	V2A	0,0830	50	0468179
47-52	1 1/2	M10	M6	20x2,0	6,0	0,95	69-74	16	96	V4A	0,133	50	0498210
53-57		M10	M6	20x2,0	6,0	0,95	75-79	16	101	V4A	0,141	50	0498211
58-64	2	M10	M6	20x2,0	6,0	0,95	80-86	16	108	V4A	0,149	50	0498212
65-70		M10	M6	20x2,0	6,0	0,95	87-92	16	114	V4A	0,160	50	0498213
72-80	2 1/2	M10	M6	20x2,0	6,0	0,95	94-102	16	123	V4A	0,171	50	0498214
82-90	3	M10	M6	20x2,0	6,0	0,95	104-112	16	134	V4A	0,186	50	0498215
93-100		M10	M6	20x2,0	6,0	0,95	115-122	16	144	V4A	0,203	50	0498216
102-107		M10	M6	20x2,0	6,0	0,95	124-129	16	152	V4A	0,216	50	0498217
108-116	4	M10	M6	20x2,0	6,0	0,95	130-138	16	160	V4A	0,225	50	0498218
47-52	1 1/2	M10	M6	20x2,0	6,0	0,95	69-74	16	96	V2A	0,132	50	0468210
53-57		M10	M6	20x2,0	6,0	0,95	75-79	16	101	V2A	0,140	50	0468211
58-64	2	M10	M6	20x2,0	6,0	0,95	80-86	16	108	V2A	0,148	50	0468212
65-70		M10	M6	20x2,0	6,0	0,95	87-92	16	114	V2A	0,159	50	0468213
72-80	2 1/2	M10	M6	20x2,0	6,0	0,95	94-102	16	123	V2A	0,169	50	0468214
82-90	3	M10	M6	20x2,0	6,0	0,95	104-112	16	134	V2A	0,185	50	0468215
93-100		M10	M6	20x2,0	6,0	0,95	115-122	16	144	V2A	0,210	50	0468216
102-107		M10	M6	20x2,0	6,0	0,95	124-129	16	152	V2A	0,214	50	0468217
108-116	4	M10	M6	20x2,0	6,0	0,95	130-138	16	160	V2A	0,224	50	0468218

Pipe clamp stainless steel, lined

Clamping range [mm]	OD [inch]	Connection	Closure screw D	Material dimension [mm]	Insulation thickness [mm]	Load F_Z [kN]	Height H [mm]	Connection height A [mm]	Width B [mm]	Material type	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
102-107		M12	M8	25x3,0	6,0	1,75	129-134	20	171	V4A	0,387	50	0490317
108-116	4	M12	M8	25x3,0	6,0	1,75	135-143	20	179	V4A	0,402	50	0490318
119-127		M12	M8	25x3,0	6,0	1,75	146-154	20	190	V4A	0,430	50	0496319
128-132		M12	M8	25x3,0	6,0	1,75	155-159	20	197	V4A	0,452	50	0496320
133-141	5	M12	M8	25x3,0	6,0	1,75	160-168	20	205	V4A	0,464	50	0496321
142-149		M12	M8	25x3,0	6,0	1,75	169-176	20	213	V4A	0,487	50	0496322
150-158		M12	M8	25x3,0	6,0	1,75	177-185	20	222	V4A	0,506	50	0496323
159-163		M12	M8	25x3,0	6,0	1,75	186-190	20	228	V4A	0,529	50	0496324
164-168	6	M12	M8	25x3,0	6,0	1,75	191-195	20	233	V4A	0,542	50	0496325
102-107		M12	M8	25x3,0	6,0	1,75	129-134	20	171	V2A	0,383	50	0460317
108-116	4	M12	M8	25x3,0	6,0	1,75	135-143	20	179	V2A	0,398	50	0460318
119-127		M12	M8	25x3,0	6,0	1,75	146-154	20	190	V2A	0,427	50	0466319
128-132		M12	M8	25x3,0	6,0	1,75	155-159	20	197	V2A	0,449	50	0466320
133-141	5	M12	M8	25x3,0	6,0	1,75	160-168	20	205	V2A	0,460	50	0466321
142-149		M12	M8	25x3,0	6,0	1,75	169-176	20	213	V2A	0,483	50	0466322
150-158		M12	M8	25x3,0	6,0	1,75	177-185	20	222	V2A	0,501	50	0466323
159-163		M12	M8	25x3,0	6,0	1,75	186-190	20	228	V2A	0,524	50	04663241
164-168	6	M12	M8	25x3,0	6,0	1,75	191-195	20	233	V2A	0,537	50	04663242
174-182		M16	M10	35x4,0	6,0	4,00	204-212	24	265	V4A	1,06	1	0490426
192-200		M16	M10	35x4,0	6,0	4,00	222-230	24	285	V4A	1,15	1	0490428
201-205		M16	M10	35x4,0	6,0	4,00	231-235	24	290	V4A	1,19	1	0490429
206-214		M16	M10	35x4,0	6,0	4,00	236-244	24	298	V4A	1,21	1	0490430
215-225	8	M16	M10	35x4,0	6,0	4,00	255-265	24	309	V4A	1,25	1	0490431
241-248		M16	M10	35x4,0	6,0	4,00	281-288	24	332	V4A	1,37	1	0492434
250-257		M16	M10	35x4,0	6,0	4,00	280-287	24	341	V4A	1,40	1	0492435
272-277	10	M16	M10	35x4,0	6,0	4,00	302-307	24	362	V4A	1,50	1	0492438
174-182		M16	M10	35x4,0	6,0	4,00	204-212	24	265	V2A	1,05	1	0462426
192-200		M16	M10	35x4,0	6,0	4,00	222-230	24	285	V2A	1,13	1	0462428
201-205		M16	M10	35x4,0	6,0	4,00	231-235	24	290	V2A	1,18	1	0462429
206-214		M16	M10	35x4,0	6,0	4,00	236-244	24	298	V2A	1,20	1	0462430
215-225	8	M16	M10	35x4,0	6,0	4,00	255-265	24	309	V2A	1,24	1	0462431
241-248		M16	M10	35x4,0	6,0	4,00	281-288	24	332	V2A	1,36	1	0462434
250-257		M16	M10	35x4,0	6,0	4,00	280-287	24	341	V2A	1,39	1	0462435
272-277	10	M16	M10	35x4,0	6,0	4,00	302-307	24	362	V2A	1,49	1	0462438
321-325		without		50x5,0	6,0	9,00	341-345		414	V4A	2,70	1	0494046
321-325	12	without		50x5,0	6,0	9,00	341-345		414	V2A	2,67	1	0464046
401-410	16	without		50x5,0	6,0	9,00	421-430		498	V2A	3,30	1	0464056