
U-bolt



U-bolt

Specification

Application area:	For direct installation of piping onto steel structures and suitable for push-through-assembling into profile rails. Suitable for sprinklerand VdS.
Recommended accessories:	nuts, washer
Type of attachment :	When used as bearing 2 nuts and 2 washer are recommended, when used as 4 nuts and 4 washers are recommended.

Technical data

Material:	Stainless steel
Material type:	V4A

Nominal width DN [mm]	Thread M	OD [mm]	OD [inch]	Center distance a [mm]	Height h [mm]	Length thread b [mm]	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
15	M8	21,3	1/2	30	85	65	0,0643	1	050602201
20	M8	26,9	3/4	35	85	65	0,0641	1	050602701
25	M8	33,7	1	42	95	65	0,0711	1	050603401
32	M8	42,4	1 1/4	51	105	75	0,0791	1	050604201
40	M8	48,3	1 1/2	57	110	75	0,0841	1	050604801
50	M10	60,3	2	71	125	75	0,152	1	050606001
65	M10	76,1	2 1/2	87	140	75	0,172	1	050607601
80	M10	88,9	3	100	155	75	0,193	1	050608901
100	M12	108,0		121	190	95	0,337	1	0506108
100	M12	114,3	4	126	195	95	0,347	1	0506114
125	M12	133,0		146	215	95	0,385	1	0506133
125	M12	139,7	5	152	220	95	0,394	1	0506140
150	M12	159,0		172	240	95	0,432	1	0506159
150	M12	168,3	6	180	250	95	0,450	1	0506168
200	M12	219,1	8	233	300	95	0,546	1	0506219