
U-bolt



U-bolt



U-bolt

Specification

Application area:	For direct installation of piping onto steel structures and suitable for push-through-assembling into profile rails. Suitable for sprinkler and VdS.
Recommended accessories:	Nuts, washer
Type of attachment :	When used as bearing 2 nuts and 2 washer are recommended, when used as 4 nuts and 4 washers are recommended.

Technical data

Material:	Steel
Surface:	galvanized

Remark: Other dimensions according to directive VdS-2092 “Planning and installation".

* VdS - G 494 0029

OD [mm]	OD [inch]	Norm	Thread M	Height h [mm]	Center distance a [mm]	Length thread b [mm]	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
21,3	1/2	similar to DIN 3570	M8	85	30	65	0,0508	100	050702201
26,9	3/4	similar to DIN 3570	M8	85	35	65	0,0623	100	050702801
33,7	1	similar to DIN 3570	M8	95	42	65	0,0701	100	050703501
42,4	1 1/4	similar to DIN 3570	M8	105	51	75	0,0781	100	050704201
48,3	1 1/2	similar to DIN 3570	M8	110	57	75	0,0823	100	050704801
60,3	2	similar to DIN 3570	M10	125	71	75	0,154	100	050706001
76,1	2 1/2	similar to DIN 3570	M10	140	87	75	0,169	100	050707601
88,9	3	similar to DIN 3570	M10	155	100	75	0,187	50	050708901
108,0		similar to DIN 3570	M12	195	121	95	0,338	50	050710801
114,3	4	similar to DIN 3570	M12	200	126	95	0,348	50	050711401
133,0		similar to DIN 3570	M12	215	146	90	0,370	25	0507133
139,7	5	similar to DIN 3570	M12	225	152	95	0,394	25	050714001
159,0		similar to DIN 3570	M12	245	172	95	0,431	25	050715901
168,3	6	similar to DIN 3570	M12	255	180	95	0,449	25	050716801
219,1	8	similar to DIN 3570	M12	300	233	95	0,525	25	0507219 *
273,0	10	DIN 3570	M20	313	302	70	1,66	10	0507273
323,9	12	DIN 3570	M20	364	352	70	1,93	1	0507324