
Hammer head screw



Hammer head screw

Specification

Application area: Direct attachment of pipe clamps to profile rails.

Type of attachment : glide fast connection

Technical data

Material: Steel

Surface: galvanized

Remark: For load specifications see end of chapter 2b.

* Not suitable for M8/M10 step thread

** Not suitable for M10/M12 step thread

Thread G	Length thread GL [mm]	Profile type	Dimension hammer head LxBxH [mm]	Thickness washer S [mm]	Ø washer D [mm]	Usable length NL [mm]	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
M8	25	22	17x17x5	2	25	9,5	0,0290	100	0692320 *
M8	40	22	17x17x5	2	25	24,5	0,0339	100	0692330
M8	20	27	24x13x4	2	25	6,3	0,0246	100	0695289 *

Hammer head screw

Thread G	Length thread GL [mm]	Profile type	Dimension hammer head LxBxH [mm]	Thickness washer S [mm]	Ø washer D [mm]	Usable length NL [mm]	Weight [kg/pc]	Packing unit [pcs.]	Part-No.
M8	30	27	24x13x4	2	25	16,3	0,0279	100	0695300
M8	40	27	24x13x4	2	25	26,3	0,0311	100	0695327
M8	30	35, Stex 35	35x18x6	3	35	12,5	0,0594	50	0697044 *
M8	40	35, Stex 35	35x18x6	3	35	22,5	0,0626	50	0697051
M8	50	35, Stex 35	35x18x6	3	35	32,5	0,0659	50	0697060
M8	70	35, Stex 35	35x18x6	3	35	52,5	0,0729	50	0697075
M10	30	35, Stex 35	35x18x6	3	35	10,5	0,0692	50	0697540 **
M10	40	35, Stex 35	35x18x6	3	35	21,0	0,0743	50	0697560
M10	50	35, Stex 35	35x18x6	3	35	31,0	0,0794	50	0697570
M10	70	35, Stex 35	35x18x6	3	35	51,0	0,0896	50	0697590
M12	35	35, Stex 35	35x18x6	3	37	14,0	0,0853	50	0698040
M12	50	35, Stex 35	35x18x6	3	37	29,0	0,0963	50	0698050
M12	70	35, Stex 35	35x18x6	3	37	49,0	0,111	50	0698070